

Combustion and Flame. Determination of spatially averaged consumption speed from spherical expanding flame: A new experimental methodology

M-E. Clavel, A. Vandel, Vincent Modica, Z. Chen, E. Varea, V. Moureau, B.

Renou

To cite this version:

M-E. Clavel, A. Vandel, Vincent Modica, Z. Chen, E. Varea, et al.. Combustion and Flame. Determination of spatially averaged consumption speed from spherical expanding flame: A new experimental methodology. Combustion and Flame, 2022, 235, pp.111720. 10.1016/j.combustflame.2021.111720. hal-03706136

HAL Id: hal-03706136 <https://normandie-univ.hal.science/hal-03706136>

Submitted on 26 Nov 2023

HAL is a multi-disciplinary open access archive for the deposit and dissemination of scientific research documents, whether they are published or not. The documents may come from teaching and research institutions in France or abroad, or from public or private research centers.

L'archive ouverte pluridisciplinaire **HAL**, est destinée au dépôt et à la diffusion de documents scientifiques de niveau recherche, publiés ou non, émanant des établissements d'enseignement et de recherche français ou étrangers, des laboratoires publics ou privés.

Combustion and Flame

Determination of spatially averaged consumption speed from spherical expanding flame: a new experimental methodology.

--Manuscript Draft--

Determination of spatially averaged consumption speed from spherical expanding flame: a new experimental methodology.

M-E. Clavel^{a,c}, A. Vandel^a, V. Modica^a, Z. Chen^b, E. Varea^a, V. Moureau^a, B. Renoua,[∗]

^aNormandie Univ., UNIROUEN, INSA Rouen, CNRS, CORIA, 76000 Rouen, France ^b SKLTCS, CAPT, BIC-ESAT, College of Engineering, Peking University, Beijing 100871, China

^cSafran Aircraft Engines Villaroche, 77550 Moissy-Cramayel, France

Abstract

Facilities using spherically expanding flame in closed vessels are generally used to report laminar burning velocities from extrapolated stretched flame speed. Considering the 1D planar reference case, flame displacement speed and consumption speed are rigorously identical. This is not true considering spherically expanding flames. While the flame displacement speeds are defined from a kinematic point of view, the consumption speed is linked to the integral of the reaction rate across the flame front. The latter is defined from a kinetic reference frame. Even though spherically expanding flames have been studied for decades, it is still challenging to experimentally determine the consumption speed. Recent developments define analytical expressions for the consumption speed and suggest experimental determination. One of the major issues consists in measuring the temporal evolution of the fresh gas density while the flame expands. In this work, an optical PIV-based method is developed to directly determine the fresh gas density ahead of the flame front and then the spatially averaged consumption speed. For the first time, experimental measurements of flame displacement speeds relative to fresh gases and burned gases, and spatially averaged flame consumption speeds are then reported for

Preprint submitted to Journal of LATEX Templates August 25, 2021

[∗]Corresponding author:

Email address: renou@coria.fr (B. Renou)

methane/air flames at different equivalent ratios. Experimental measurements are systematically compared with DNS which simulates the experimental geometry. A very good agreement is observed between experimental and numerical data irrespective to the equivalence ratio, underlying the robustness of the experimental methodologies. Finally, the sensitivity of the different flame speeds to flow confinement and extrapolation models is discussed.

Key words: Laminar burning velocity, Spherically expanding flames, Stretch effects, Consumption speed, Displacement speed

1. Introduction

The development of new kinetic schemes requires efficient validation on ignition delays time, major and/or minor species profiles and unstretched laminar burning velocity $S_L⁰$ data. For 1D unstretched planar premixed flame, S_L^0 represents the rate at which the fresh gases are consumed through the flame front. By integrating the transport equation of the fuel mass fraction through the flame domain, one can derive the expression of the laminar burning velocity for 1D planar flames [\[1\]](#page-37-0),

$$
S_L^0 = \frac{1}{\rho_u \left(Y_{F,b} - Y_{F,u} \right)} \int_{-\infty}^{+\infty} \dot{\omega}_F dx \tag{1}
$$

where ρ_u is the fresh gas density, $\dot{\omega}_F$ is the fuel reaction rate and $Y_{F,b}$ and $Y_{F,u}$ are the fuel mass fractions in burned and fresh gases, respectively. The upper script 0 refers to the 1D and unstretched conditions. From Eq. [\(1\)](#page-3-0), the laminar burning velocity $S_L⁰$ is equivalent to a *consumption speed* and corresponds to the fuel mass rate which enters the flame front. This expression of the laminar burning velocity is valid for any major species k . For the 1D planar ¹⁵ configuration, the laminar burning velocity can also be defined as a kinematic quantity which is called the *density weighted flame displacement speed* [\[2\]](#page-37-1),

$$
\widetilde{S}_d^0 = \frac{\rho}{\rho_u} \left(\mathbf{S_f} - \mathbf{u} \right) \cdot \mathbf{n} = S_L^0 \tag{2}
$$

The density-weighted displacement speed is defined to a specified temperature iso-surface. The temperature gradient defines the unit normal n to the flame surface, with n pointing towards the fresh reactants. $S_f = \mathbf{S_f} \cdot \mathbf{n}$ ²⁰ is the absolute flame speed or propagation speed, and $u = \mathbf{u} \cdot \mathbf{n}$ is the local flow velocity normal to the temperature iso-surface. ρ is the local flow density obtained at the flame iso-surface where u is defined.

Laminar burning velocity is one of the few fuel parameters which can be experimentally measured at relevant conditions for engines or combustion chamber applications [\[3\]](#page-38-0). Among the different techniques, experimental facility using spherically expanding flame is generally chosen as it offers flexibility in terms of initial conditions.

Several methods have been developed to measure flame speeds from expanding flames in confined vessels. They should be considered as complementary.

The constant volume method is quite old and makes it possible to obtain flame speed values for high pressure and temperature conditions from the time analysis of the pressure signal in the combustion chamber and from a thermodynamic model for the mass fraction of burnt gases. Recently, experimental and numerical works have provided original solutions to overcome these models and demonstrated the potential of this method [\[4–](#page-38-1)[6\]](#page-38-2).

The constant pressure method is widely used for a broad range of operating conditions (including low pressure) and fuel compositions. For this approach, spherical expanding flames are stretched due to the interaction between flame ⁴⁰ propagation and flow, and $S_L⁰$ is reported using extrapolation procedures to zero stretch. Discussions about linear and non-linear models can be found in [\[7\]](#page-38-3) for instance, and effects of finite flame thickness in extrapolation models in [\[8,](#page-38-4) [9\]](#page-38-5).

In the following, all the developments concern the constant pressure method. In constant pressure method, unstretched laminar burning velocity is commonly

reported from density-weighted displacement speed relative to the burned gases,

$$
\widetilde{S_{d,b}} = \frac{\rho_b}{\rho_u} \left(\mathbf{S_f} - \mathbf{u_b} \right) \cdot \mathbf{n} \tag{3}
$$

This equation is systematically simplified into,

$$
\widetilde{S_{d,b}} \simeq \frac{\rho_b^{eq}}{\rho_u} \frac{dR}{dt} \tag{4}
$$

where ρ_b^{eq} is the burned gas density at adiabatic thermodynamic and chemical equilibrium conditions. dR/dt is the absolute flame speed, S_f , deduced from the time derivative of the flame radius, R . R is experimentally obtained from high-speed schlieren, shadowgraphy or tomographic recordings. Note that the burned gases are assumed to be at rest $(u_b = 0)$. So, in these conditions, Eq. [\(4\)](#page-5-0) becomes the easiest way to experimentally determine the laminar burning velocity. However, the hypothesis required to reach this formulation are sometimes not fully verified, involving many biases on the $S_L⁰$ determination. Indeed, for small combustion chamber [\[10\]](#page-38-6), for low pressure [\[11\]](#page-39-0) and when radiation is non-negligible [\[12\]](#page-39-1), these approximations fail and other experimental approaches are necessary.

Recent developments in PIV post-processing [\[13–](#page-39-2)[15\]](#page-39-3) allow to directly measure the local fresh gas velocity, u_u , ahead of the flame front. This region is characterized by high local velocity gradient, which makes the measurements very difficult to perform. New algorithms were developed and the density weighted displacement speed relative to the fresh gases, $\widetilde{S_{d,u}}$, can be now experimentally determined,

$$
\widetilde{S_{d,u}} = \left(\frac{dR}{dt} - u_u\right) \tag{5}
$$

The fresh gas velocity u_u is approximated experimentally by the maximum of ⁶⁵ fresh gas velocity which occurs at the entrance of the preheat zone. $S_{d,u}$ allows a direct measurement of laminar flame speed, without assumptions on the state of the burned gases, and on the velocity field. This approach must be considered

to report laminar flame speed when conditions required to use Eq. [4](#page-5-0) fail. Consequently, the two kinematic approaches (Eqs. [3](#page-5-1) and [5\)](#page-5-2) are complementary and must be used together to address the difficult task to measure laminar burning velocity with the constant-pressure method.

The two previous flame speed definitions are related to kinematic information. It is however possible to introduce the consumption speed based on the integral of the reaction rate. Similar to 1D condition (Eq. [1\)](#page-3-0), a local consumption speed can be introduced and calculated in spherical expanding flames [\[16\]](#page-39-4). This definition is appropriate for unidirectional flows, e.g., planar or spherical flames, where the normal to the flame is properly defined, but it can not be measured experimentally. To overcome this difficulty, the spatially averaged consumption speed was introduced a long time ago by normalizing the global consumption rate, obtained by integrating the fuel reaction rate throughout the entire combustion volume by the flame surface area. Fiock and Marvin [\[17\]](#page-39-5), Bradley and Mitcheson [\[18\]](#page-39-6) or more recently Bonhomme et al. [\[19\]](#page-39-7) developed theoretical approaches for the spatially averaged consumption speed of the deficient species. Lefebvre et al. [\[20\]](#page-40-0) recently developed a generalized $\frac{1}{85}$ expression for any major species k. However, the authors concluded that only the equation of deficient species can be experimentally used since it does not require the determination of ambiguous burned gas parameters such as ρ_b or the mass fraction of species k in the burned gases. These parameters are not necessarily spatially homogeneous and are almost difficult to measure. The expression of the spatially averaged consumption speed for the deficient species k is [\[20\]](#page-40-0),

$$
\langle S_c \rangle = \langle S_{c,k} \rangle = S_f - \frac{(R_0^3 - R_{f,k}^3)}{3R_{f,k}^2} \frac{1}{\rho_u} \frac{d\rho_u}{dt}
$$

$$
= -\frac{1}{\rho_u Y_{k,u} R_{f,k}^2} \int_0^{R_0} \dot{\omega}_k r^2 dr \tag{6}
$$

where $R_{f,k}$ is an equivalent flame radius based on the integral of a progress

variable based on the partial density of species k and the radius. $R_{f,k}$ is given by

$$
R_{f,k} = \sqrt[3]{\int_0^{R_0} \left(1 - \frac{\rho Y_k}{\rho_u Y_{k,u}}\right) 3r^2 dr}
$$
 (7)

 \mathcal{P}_{95} In this equation, R_0 is the combustion chamber radius. Consequently, the spatially averaged consumption speed $\langle S_c \rangle$ corresponds to the global consumption rate normalized by the surface defined by the radius $R_{f,k}$ based on the total mass of species k contained into the sphere of radius $R_{f,k}$. For lean and stoichiometric mixtures, $k =$ Fuel, and for rich conditions, $k =$ O_2 . It was recently shown that the isotherm corresponding to the flame radius $R_{f,k}$ is very closed to that of experimental radius obtained by laser tomography [\[20\]](#page-40-0). This spatially averaged consumption speed is therefore not exactly equal to the local consumption speed (Eq[.1\)](#page-3-0) [\[16\]](#page-39-4), but it represents a convenient way to experimentally report the global fuel consumption rate, from scalar measurements. A promising method to measure the spatially averaged consumption speed in a closed vessel was presented in the numerical work of Bonhomme et al. [\[19\]](#page-39-7). The authors proposed to combine both the temporal evolution of the flame radius $R_f(t)$ and the internal chamber pressure $P(t)$ assuming an isentropic compression for the fresh gases, as

$$
\frac{1}{\rho_u} \frac{d\rho_u}{dt} = \frac{1}{\gamma_u P} \frac{dP}{dt}
$$
\n(8)

The spatially averaged consumption speed yields

$$
\langle S_c \rangle = \frac{dR_f}{dt} - \frac{(R_0^3 - R_f^3)}{3R_f^2} \frac{1}{\gamma_u P} \frac{dP}{dt}
$$
\n
$$
\tag{9}
$$

Prima facie, Eq. [9](#page-7-0) seems to be a good candidate for the evaluation of the consumption speed as it only requires the temporal evolution of the flame radius and the pressure signal $P(t)$. However, from an experimental point of view, the values of the consumption speed could lack accuracy since this formula is based on the difference of two large numbers. This was originally

mentioned by Andrews and Bradley [\[21\]](#page-40-1). Therefore, the experimental accuracy of the pressure measurement must be excellent to avoid any noise during the time derivative computation of the pressure signal. It implies that the pressure sensor has to be accurate enough during the early stages of flame development (pre-pressure period), where the pressure rise is very small (in the range of hundreds Pascal) and at the same time, the pressure sensor must also be capable of withstanding high pressure loads due to the combustion process in a constant volume chamber. From these observations, the consumption speed can therefore be estimated from Eq. [\(6\)](#page-6-0) where the fresh gas density needs to be evaluated, or from Eq. [\(9\)](#page-7-0) where the pressure trace needs to be accurately recorded.

The aim of this study is therefore three-fold:

- First, a new experimental approach to estimate the instantaneous density field ahead of the flame front is developed and used to report the spatially averaged consumption speed for spherical expanding flames. It is based from the mass conservation written for a material control volume, and requires the measurement of the local fresh gas velocity. This methodology is validated by comparing DNS simulations of laminar spherically expanding flame and experimental data for methane/air mixtures (lean, rich and stoichiometric).
- The experimental methodology initially developed by [\[14\]](#page-39-8) to report fresh gas velocity profile ahead of the flame front is reconsidered and improved, to provide more accurate data. An extensive work of optimization of post-processing routines, camera properties and laser frequencies are conducted on classical methane/air mixtures at atmospheric conditions. A direct comparison with DNS data is also performed to assess the quality of the post-processing steps.
- Finally, the suitability of the spatially averaged consumption speed 145 formulation $(\langle S_c \rangle)$ and kinematic approaches $(\widetilde{S_{d,u}}$ and $\widetilde{S_{d,b}})$ for lean, rich

-
-

and stoichiometric methane/air flames is discussed from both experimental and numerical data.

2. Experimental and numerical apparatus

In this section, the experimental setup for flame speed measurements is briefly described. Details on the numerical simulations performed with the DNS code (A-SURF) are also presented.

2.1. Experimental setup

The apparatus and post-processing methods are described in detail in [\[14,](#page-39-8) [22\]](#page-40-2) and are briefly reminded. Experiments are conducted in a spherical stainless 155 steel combustion chamber with an equivalent chamber radius $R_0 = 8.243$ cm. The mixture is seeded with micronical silicon oil droplets with a theoretical boiling temperature of $T = 580K$. High-speed laser tomography technique is used to capture the temporal evolution of the flame front and particle images by using a circle least-square fitting method. A double cavity Nd:YLF laser 160 (Darwin Dual, Quantronix), delivering 6 mJ pulses at 527 nm and at 5 kHz , is used to illuminate seeding particles. A high-speed camera (Photron Fastcam SA1.1) records 12-bit images of 1024×1024 pixels² at the same frequency of $5 kHz$. The camera is perpendicular to the laser sheet. The magnification ratio is set to 0.04746 mm/px. In addition to the measurements from optical diagnostics, the pressure trace is recorded during the flame propagation using a dynamic pressure transducer Kistler 7001, directly placed into the vessel in order to avoid disturbance or attenuation. This sensor, which has a natural frequency of 70 kHz , has been selected since it fits as best as possible the existing setup while keeping the best dynamics. Moreover, the sensor is resistant enough to high pressure loads. For each experimental condition, experiments are performed 10 times and all values of stretched flame speeds are based on these series of 10 measurements. Methane/air mixtures are investigated for very lean (ϕ = 0.7), stoichiometric and rich (ϕ = 1.2) conditions, with a pressure of 1 atm and a temperature of 293K.

2.2. Numerical simulation with A-SURF code

Spherical flame propagation is simulated using the DNS code A-SURF. The simulation domain reproduces the experimental apparatus described above in terms of chamber geometry and thermodynamical properties. A-SURF solves the one-dimensional, unsteady, compressible, conservation equations for a multi-component reactive flow in spherical coordinates using the finite volume method. The details on governing equations, numerical schemes, and code validation can be found in [\[23\]](#page-40-3). Simulations are performed for CH_4/air flames with the GRI-mech 3.0 kinetic scheme [\[24\]](#page-40-4). It is noted there are several recent kinetic models for methane oxidation. According to Wang et al. [\[25\]](#page-40-5), there is good agreement among laminar flame speeds predicted by different mechanisms for ambient conditions and large discrepancy appears only for engine-relevant conditions with pressure above 20 atm. Since here we consider the ambient conditions for which GRI-mech 3.0 was optimized, GRI-mech 3.0 is used in our simulations. Initial conditions are atmospheric thermodynamic conditions,

 $i.e.$ a temperature of 293 K and a pressure of 1 atm. In all the simulations, the mixture is initially static. In order to maintain adequate resolution of the propagating flame, dynamically adaptive mesh is utilized in A-SURF with a finest grid size of 8 μ m. It is noted that radiation heat loss is not considered here. Since the equivalence ratios are not close to the flammability limits of methane/air mixtures and the corresponding laminar flame speeds are above 15 cm/s, radiation heat loss has negligible effect on propagating spherical flames whose radii are below 2 cm [\[26\]](#page-40-6). This DNS database will be used for a direct and blind comparison with the different laminar flame speeds reported from the experiments, and the validation of the post-processing routines as well.

 Unstretched laminar burning velocities are computed by Cantera [\[27\]](#page-40-7) from the one-dimensional freely-propagating configuration, by using the same kinetic scheme [\[24\]](#page-40-4) and the same operating conditions $(T = 293 K, P = 1 atm)$. In these simulations, the mixture-averaged diffusion model is considered. The computational domain is from 0 to 5.0 cm. The minimum values of the gradient and curvature for the last iteration are set to 0.02.

3. Measurements of fresh gas velocity profiles ahead of the flame front

3.1. Principles

An in-house PIV post-processing technique is used to compute the fresh gas velocity field ahead of the flame front, to report $\langle S_c \rangle$ and $\widetilde{S_{d,u}}$. For two ²¹⁰ successive tomographic images where the flame radius R_T can be extracted, the algorithm defines a region of interest (ROI) around the spherical flame. The ROI is an angular sector of the fresh gases with an angle θ which is adjusted to 320 \degree which fits the flame contour of a radius R_T . The width of the ROI is restricted to 110 pixels $(5.22 \, mm)$, where the velocity profiles are measured (Figure [1\)](#page-12-0). This ROI is then dewarped into a Cartesian coordinate system using a bilinear interpolation scheme. An interrogation window (IW) with a width varying from 1 to 5 pixels is located within this ROI. A matching method based on a two-dimensional normalized cross-correlation is used between IWs of the two successive ROIs. First, the best correlation between both IWs is obtained by shifting only the first IW in increments of one pixel in the direction normal to the flame front. The location of the maximum of correlation (Δr_1^{opti}) obtained from a sub-pixel fit (7 points Gaussian) gives the fresh gas velocity u ahead of the flame front at the location of the first IW, so that

$$
u(t^*, \Delta r_2) = \frac{R_T(t^* + \Delta t) - R_T(t^*)}{\Delta t} + \frac{\Delta r_2 - \Delta r_1^{opti}(t^*)}{\Delta t}
$$
(10)

where $R(t^*)$ and $R(t^* + \Delta t)$ are the flame radii at time t^* and $t^* + \Delta t$, Δt is the time between two successive images and Δr_1^{opti} is the optimum displacement of the first IW obtained for the displacement of the second IW, Δr_2 . Fixing the second IW and searching the best correlation on the first one avoids problems of evaporated droplets. To characterize the velocity profile ahead of the flame, the second stage of post-processing consists in moving the second IW by step 230 of one pixel (Δr_2) in the direction normal to the flame front. For each position of this window, the first step of the template matching procedure is restarted. Original details of the procedure can be found in [\[14\]](#page-39-8). There is a compromise to find on the thick of the interrogation window (IW) in the ROI. The thicker

the IW, the better the correlation since much more droplets will be included in the correlation. But the spatial filtering of the velocity profiles will be more important and the maximum of the velocity profile would not be captured. We did several tests, and the conclusions give that the compromise is at 2 pixels. It is worth noting that the first term in the right hand side of Eq. [10](#page-11-0) is equal to the flame propagation speed $S_f \cdot n$ approximated by finite difference.

Figure (1) Sketch of flame kernel propagation in the confined combustion chamber of radius R_0 . (a) A quarter of the flame with a flame thickness δ_L is represented. The red curve is associated to the flame contour obtained by laser tomography and corresponds to the oil droplet evaporation isotherm. (b) A 1D view of a dewarped tomographic image with the corresponding tomographic flame radius R_T . The control volume used for the determination of fresh gas density is represented with yellow dotted lines. (c) Similar dewarped tomographic images at two successive times used for the determination of the fresh gas velocity profiles ahead of the flame front. The ROI is represented by a yellow dotted line rectangle and the IW is the gray zone with an adjustable width of 1-5 pixels.

3.2. Improvement and validation of the experimental methodology

The availability of the DNS database is a good opportunity to revisit and optimize the post-processing routines which were originally developed in [\[14\]](#page-39-8). First, we address the question of the tomographic image post-processing, since the image quality impacts strongly the contour detection and correlation processes. An automatic contrast adjustment procedure of tomographic images is performed by using a linear stretching of intensity range. At the same time, laser sheet in-homogeneity is corrected by using temporally averaged seeded

tomographic recordings (without flames). Consequently, black and white are saturated to make flame front detection easier and particles more identifiable.

- In a second step, the interval time between two-successive images must be considered since it may impact the accuracy of the distance Δr between the value of the optimum displacement of the first IW $\Delta r_1^{opti}(t^*)$ with the value of the displacement of the second IW Δr_2 (Second term of the RHS in Eq. [10\)](#page-11-0). The classical problem of correlation peak fitting procedure is clearly evidenced
- in Figure [2,](#page-14-0) where different correlograms have been obtained for different values of Δt . The laser frequency is kept constant at $f = 5000Hz$, and the images are processed with a $\Delta t = n/f$, n varying from 1 to 4. For each, a basic 7-points Gaussian fit is used to report the values of $\Delta r_1^{opti}(t^*)$. The lower the interval time Δt , the smaller the values $\Delta r_1^{opti}(t^*)$, and the greater the impact of the accuracy of the sub-pixel position of the maximum correlation peak on $\Delta r_1^{opti}(t^*)$. However, a high interval time may act as a low-pass spatial filtering when computing the fresh gas velocity which may fail to capture the maximum flow velocity. From our operating conditions, the best compromise seems to get a minimum value of Δr around 3 pixels which ensure a acceptable uncertainty and a spatial resolution of the velocity profile. Consequently, image frequency (nominal frequency or a fraction of the nominal frequency) is selected according to the flame propagation speed values for a specific operating conditions.
- From the last improvements which have been discussed previously, some numerical and experimental profiles of the fresh gas velocity are reported in Figure [3](#page-16-0) for two different equivalence ratios and two different flame radii. These selected plots are representative of the experimental measurements. At the same time, numerical temperature profiles are plotted. Due to inherent time shift from the numerical initialization of the flame kernel, computations and experimental data are time-scaled for a similar radius. The shift in time is as low as 200 μs which is more or less one experimental time step. The experimental velocity profiles obtained from the methodology presented above are plotted with black open circles. The fresh gas velocity at the entrance of
	- the flame front, u_u , is obtained from the maximum (filled red diamond) of a

Figure (2) Correlation peaks (open circles) and corresponding 7-points Gaussian fit (continuous lines) for different interval times between two successive images. Value of Δr_2 is set to 7 pixels, corresponding to a location in the fresh gas velocity profiles close to the maximum values. Results for $\phi = 1$, and $t^* = 7.0$ ms

 $6th$ order polynomial fit from the first point to 1.3 mm (continuous red line). 280 The experimental velocity data, $u(r)$, in the decreasing zone (green zone) is fitted with the theoretical model suggested by Poinsot et al. [\[1\]](#page-37-0), following a $(R_0^3 - r^3)/r^2$ shape. Simultaneously, the experimental and numerical radii at the maximum fresh gas velocity are reported for a quantitative comparison between experiments and simulations. This figure highlights the capability of the experimental methodology to report the gas velocity profiles both for the fresh gas side and in the preheat zone up to the evaporation of oil droplets accurately. The spatial resolution of the measurements is high enough to capture the maximum of the gas velocity which occurs at the entrance of the preheat zone. The interval times in two successive images have been adapted such as the particle displacement at the maximum velocity profiles remains close to 3 pixels, as suggested above. One can notice also the perfect agreement of the experimental profiles with the numerical data.

Regarding Fig. 3, it is clear that the maximum of fresh gas velocity doesn't peak exactly at T_u but at a slightly higher temperature. Numerical data analysis

295 shows that this temperature is around 310 K and remains almost constant as the flame propagates. This is very similar to the results presented in [\[28\]](#page-41-0). Consequently, the experimental displacement speed corresponds to

$$
\widetilde{S_{d,u}^{Exp}} = \left(\frac{dR}{dt} - u_{g,max}\right) \tag{11}
$$

where $u_{g,max}$ is the velocity at which the fresh gas velocity is maximum. We assume implicitly equality between the definition of $\widetilde{S_{d,u}}$ from Eq. [5](#page-5-2) and $\widetilde{S_{d,u}^{Exp}}$ from Eq. [11.](#page-15-0) This observation underlines also the difficulty to select the fresh gases iso-surface when considering the displacement speed relative to the fresh gases as it was originally discussed by Gianakopoulos et al. [\[2\]](#page-37-1) and Jayachandran et al. [\[28\]](#page-41-0). The choice of the fresh gas temperature as a reference location for the determination of $S₍d, u)$ is poorly conditioned and should be used with care. However, even with this limitation, this approach must be considered as a complementary to the classical methodology that might introduce issues due to unknown fuel chemistry and burned gas composition, differential diffusion or radiation effects, and low pressure as mentioned in the work of Varea et al. [\[29\]](#page-41-1), Jayachandran et al. [\[30\]](#page-41-2) and Faghih et al. [\[11\]](#page-39-0). It is worth noting that this method is also limited by the flame thickness. The thinner the flame front, the more difficult it becomes to capture and spatially resolve the maximum velocity. Consequently, this approach is not suited for high pressure conditions but it is rather well adapted for low pressure conditions (large flame thickness), when the assumptions used to apply Eq. [4](#page-5-0) fail.

Figure (3) Fresh gas velocity and temperature profiles from experimental and numerical data, for two different operating conditions. (Top) Methane/air flame ($\phi = 0.7$ and $R_T =$ 15.2 $mm)$ and (Bottom) Methane/air flame $(\phi=1.0$ and R_T = 19.8 $mm)$

315 4. A new tool to determine the fresh gas density in freely propagating spherical expanding flames

4.1. Theoretical developments

From its definition, the fresh gas density corresponds to the ratio between the mass of fresh gases and the volume it occupies. The temporal evolution of the fresh gas density can be estimated by determining the flux entering and/or leaving through the edges of a fixed volume. This flux is directly linked to the fresh gas velocity, a quantity which can be measured from PIV experiments. However, operating with a fixed volume is problematic since the flame propagates and might reach the edges of the fixed volume, therefore leading to unsuccessful PIV post-processing. Consequently, another type of analysis must be considered. In the present study, we propose to integrate the continuity equation in space considering an arbitrary volume $V_a(t)$ to allow an estimation of the fresh gas density temporal evolution, $\rho_u(t)$, while the flame expands. Let's consider a material control volume $V_m(t)$. The latter is defined such as it moves with the fluid so that the velocity at one point of its bordering surface is equal to the local fluid velocity U . The mass conservation equation without sources or sink terms is

$$
\frac{d}{dt} \int_{V_m(t)} \rho dV = 0 \tag{12}
$$

According to the transport theorem, an arbitrary control volume $V_a(t)$ which coincides with $V_m(t)$ at time t but doesn't necessarily move at the fluid velocity can be introduced and Eq. [\(12\)](#page-17-0) is

$$
\frac{d}{dt} \int_{V_m(t)} \rho \ dV = \frac{d}{dt} \int_{V_a(t)} \rho \ dV + \oint_{A_a(t)} \rho \left(\mathbf{u} - \dot{\mathbf{X}} \right) . \mathbf{n} dA \tag{13}
$$

where $\dot{\mathbf{X}}$ is the local velocity of the area $A_a(t)$ bordering the volume $V_a(t)$ and u is the fluid velocity at the location X. Using an arbitrary volume is more convenient in experiments since the boundaries of the surface can be well selected. The sketch in Fig. [1](#page-12-0) shows a spherical volume (only a quarter is

 340 represented) which uniquely contains fresh gases from a radius $R = X$ to the vessel wall at $R = R_0$. Note that X is adjusted so that the distance d to the flame front is kept constant at each time step. Integrating Eq. [\(13\)](#page-17-1) between time t^n and t^{n+1} yields

$$
\frac{\left(\int \rho \ dV\right)^{n+1} - \left(\int \rho \ dV\right)^n}{t^{n+1} - t^n} - \oint_{A_a(t^{n+1/2})} \rho \left(u - \dot{X}\right) dA = 0 \tag{14}
$$

Note that only the radial component is considered as the geometry is 345 spherical. Assuming that the density at time step $n+1/2$ is the average density between time $t = n$ and $t = n + 1$, one can estimate the temporal fresh gas density evolution at each time step as

$$
\rho_u^{n+1} = \rho_u^n \frac{\left[\frac{R_0^3 - (X^n)^3}{3\Delta t} + \frac{1}{2} \left(X^{n + \frac{1}{2}} \right)^2 \left(u^{n + \frac{1}{2}} - \dot{X}^{n + \frac{1}{2}} \right) \right]}{\left[\frac{R_0^3 - (X^{n+1})^3}{3\Delta t} - \frac{1}{2} \left(X^{n + \frac{1}{2}} \right)^2 \left(u^{n + \frac{1}{2}} - \dot{X}^{n + \frac{1}{2}} \right) \right]}
$$
(15)

with $X^{n+\frac{1}{2}} = \frac{X^{n+1} + X^n}{2}$ and $\dot{X}^{n+\frac{1}{2}} = \frac{X^{n+1} - X^n}{\Delta t}$. This equation requires the initial fresh gas density ρ_u^0 , the position X of the area $A_a(t)$ at each time step 350 and the fresh gas velocity u through the area $A_a(t)$ between two consecutive time steps. This later is available unambiguously thanks to the developments presented above. The experimental method for determining these parameters as well as its validation are presented in the next section.

4.2. Validation from DNS data

- 355 Direct numerical simulations of CH_4/air flames at atmospheric pressure and temperature are used to access the time evolution of the fresh gas density. It is worth noting that the exact same methodologies, *i.e.* post processing techniques, are used for both experimental and numerical data. This induces consistency for comparisons. From the numerical simulations, the temporal fresh gas density
- evolution is evaluated using Eq. (15) . This equation written in a discrete sense is computed with the position X which corresponds to the edge of a control volume and the velocity u of the fresh gases at this specific position X . Moreover,

from the simulations, the fresh gas density is also directly available. Therefore, one can evaluate the suitability of the Eq. [\(15\)](#page-18-0) to report the fresh gas density, directly from the DNS. The results are shown in Figure [4](#page-20-0) (Top). Note that the variables X and u have been computed from DNS data at an acquisition rate equal to the experimental one, *i.e.* $5 kHz$. A perfect agreement between the

fresh gas density from the simulations and the one calculated using Eq. [\(15\)](#page-18-0) from

the simulations are reported. This result confirms the reliability of Eq. [\(15\)](#page-18-0) to accurately determine the fresh gas density ahead of the flame front. Moreover, an acquisition rate of $5 \; kHz$ seems to be sufficient enough to describe well the temporal evolution of the fresh gas density. In Eq. [15,](#page-18-0) the parameter X is defined according to the flame front position so that $X = R_T + d$, where d is a constant. The distance d should be set to avoid the influence of the preheat zone, so that the velocity profile displays a decreasing behavior, following a $1/R^2$ shape. This condition is satisfied when $d \geq 1-2$ mm. Effects of larger values d on the calculation of the compression term $1/\rho_u \cdot d\rho_u/dt$ are reported in Fig. [4](#page-20-0) from the simulations. Relative differences of the rate of change of the fresh gas density calculated at $d = 1.2$ mm and $d = 3.5$ mm are marginal, and demonstrate very negligible effects of the distance d on the compression term. For the experimental determination of ρ_u , the distance d will be set to 70 pixels $(3.3 \, mm)$. This value of $d = 70$ pixels is extracted from the velocity profile fit in Figure [3](#page-16-0) and corresponds to the green fill diamond.

4.3. Application to experimental data and validation

 Experimental data are processed to estimate the temporal evolution of the fresh gas density from Eq. [\(15\)](#page-18-0). The main difficulty remains in the ability to accurately measure the parameter X, the position of the area $A_a(t)$ at each time step, and u, the fresh gas velocity through the area $A_a(t)$ between two consecutive time steps. Both experimental and numerical data of the 390 compression term $1/\rho_u \cdot d\rho_u/dt$ plotted against the flame radius are reported in Fig. [5](#page-22-0) for different equivalence ratio. Note that the experimental repeatability –shot-to-shot variation– is shown by plotting the 10 experimental trials. A

Figure (4) (Top) Relative difference of the numerical fresh gas density ρ_u calculated by Eq. [15](#page-18-0) using DNS data and directly extracted from DNS database $(\phi = 1)$. (Bottom) Influence of the position d on the evaluation of the compression term $1/\rho_u \cdot d\rho_u/dt$ of fresh gases. The relative difference of the value of this compression term computed with distance from tomographic radius $d = 3.5$ mm and $d = 1.2$ mm is reported as a function of the flame radius.

- perfect agreement is reported as both the experimental and numerical data do overlap. From the previous statements, both the repeatability of experimental data as well as the accuracy of the post-processing techniques to access the compression term of Eq. [\(15\)](#page-18-0) are demonstrated. From the thermodynamic perspective, the rate of change of the fresh gas density is linked to the rate of change of the pressure assuming isentropic compression, see Eq. [\(8\)](#page-7-1). Figure [5](#page-22-0) reports also experimental data for the compression term. Data corresponding to the time derivative of the pressure trace – isentropic compression – are widely dispersed. Therefore no trend of the rate of change of the pressure trace can be distinguished neither computed. The data lead to a high level of inaccuracy. It is worth noting that the accuracy of the pressure signal is responsible for this. Since the increase of the pressure signal is a low as 3 percents for a typical flame 405 (radius of 2 *cm* for a stoichiometric CH_4/air flame), no pressure transducers
- were found to deal with small signal detection, high frequency sampling, huge

scaling range – up to several bar – and still affordable setup. Therefore, it clearly appears that the measure of the pressure signal for the evaluation of the compression term and the evaluation of Eq. [\(9\)](#page-7-0) is not relevant enough. From an experimental point of view, there is no possibility to achieve a reliable evaluation of the consumption speed assuming isentropic compression hypothesis when considering the constant pressure method in spherical expanding flames.

4.4. Experimental uncertainties on stretched flame speeds

Experimental uncertainties on the different stretched flame speeds are computed as follows. First, we need to consider the uncertainties relative to the operating conditions, mainly the initial mixture temperature, pressure, equivalence ratio and spark energy. In addition to the intrinsic accuracy of each sensor, the initial conditions can be slightly different from one experiment to another. For this study, we consider a maximal variation of ± 1.5 K, ± 0.001 bar $_{420}$ and $\pm 1\%$ for initial temperature, pressure and equivalence ratio, respectively. Spark energy, shape and volume may change also slightly from one ignition to another one. These four sources of uncertainties may impact the flame dynamic, and their contribution to the different flame speeds will be estimated by performing a statistical analysis with a number of flame recordings per 425 condition, $N \geq 10$. The second source of uncertainty comes from the image processing steps for each flame recording. Both flame radius and fresh gas velocity determination from tomographic recordings are associated to individual uncertainties coming from the capability of the routines to extract the quantities of interest from noisy signals. The uncertainty of flame radii is estimated for each flame contour by considering the relative distance between the flame contour and the circle fit based on the least-square method. The mean relative uncertainty over all the images is on the order of 0.03%. The uncertainty on the maximum fresh gas velocity u_u includes the contribution of the sub-pixel fit of correlation peak, the uncertainty in the flame front position after dewarping, and the contribution of the six degree polynomial fit of the fresh gas velocity profile. The mean relative uncertainty of u_u over all the images is on the order of 0.5%. Once

Figure (5) Comparison of the fresh gas density compression term from simulations and experimental data (based from more than 10 different flames) with respect to the experimental flame radius, for lean (Top), stoichiometric (Middle) and rich (Bottom) conditions. Comparison between the terms $1/\rho_u \cdot d\rho_u/dt$ and $1/\gamma_u P \cdot dP/dt$ for experiments when $\phi = 1.0$.

these uncertainties are evaluated, they are propagated when flame stretch and the different flame speeds are computed, according to methodology suggested by [\[31,](#page-41-3) [32\]](#page-41-4). Consequently, for each test, a one σ uncertainty is computed for 440 each instantaneous stretched flame speed S, hereafter $e(S)$, where S is either $\widetilde{S_{d,b}}, \widetilde{S_{d,u}}$ or $\langle S_c \rangle$.

In the next section, the contribution of these two sources of uncertainties on the different flame speeds is reported as follows. All the instantaneous stretched flame speeds S_k are averaged per class of stretch of $8s^{-1}$ over the N tests, weighted by their respective instantaneous uncertainty $e^2(S_k)$, according to [\[31,](#page-41-3) [32\]](#page-41-4):

$$
\overline{S} = \frac{\sum_{k} \frac{S_k}{e^2(S_k)}}{\sum_{k} \frac{1}{e^2(S_k)}}
$$
(16)

The corresponding variance is :

$$
\sigma^2(\overline{S}) = \frac{1}{\sum_k \frac{1}{e^2(S_k)}}\tag{17}
$$

Finally, an expanded uncertainty $U(\overline{S})$ of the averaged speed \overline{S} is calculated from this variance $\sigma^2(\overline{S})$, and a coverage factor k, calculated from a Student's 450 law based on the number of value used on the average process $(k > 10)$, and on a level of confidence of 95%.

$$
U(\overline{S}) = k\sigma(\overline{S})\tag{18}
$$

Consequently, \overline{S} will be plotted according to stretch with error bars equal to $\pm U(\overline{S})$, that encompass large fraction (95%) of the distribution of values that could reasonably be attributed to \overline{S} . Obviously, the higher the number of flame 455 recordings per condition, the lower the $\sigma(\overline{S})$.

In the following sections, stretch flame speeds, \overline{S} , will be fitted with linear or non-linear models using the least squares method to find the extrapolated flame

speed and the corresponding Markstein length. The uncertainty on these two parameters is estimated from the covariance matrix of the fit and the dispersion of the residuals. All these data are reported in different tables below.

5. Flame speed evaluations, and direct comparison with DNS

In this section, the three different stretched flame speeds are experimentally evaluated according to the previous developments for $CH₄/air$ flames at three different equivalence ratios. Extrapolated values are also compared ⁴⁶⁵ with numerical laminar burning velocity $S_L⁰$ obtained from Cantera (freely propagating 1D flame, with GRI3.0). Each comparison is followed by discussions about the relevance of the methodology and the potential use of these flame speeds for both laminar flame speed determination and use in some applications. $S_{d,b}$ is first presented to illustrate the capability of the DNS to reproduce the flame dynamic in that geometrical configuration. From that preliminary comparison, $S_{d,u}$ is then discussed, followed by the new developments made to estimate the spatially averaged consumption speed $\langle S_c \rangle$.

5.1. Displacement speed relative to burned gases, $\widetilde{S_{d,b}}$

Figure [6](#page-26-0) presents a direct comparison of density weighted displacement speed relative to burned gases for lean, rich and stoichiometric conditions. Flame speeds are plotted versus flame stretch from ignition to the maximum flame radius which can be experimentally observed. In order to avoid ignition and confinement effects, a restricted range of flame stretch must be chosen for extrapolation. There is a general agreement to select a minimum flame radius of 10 mm and a maximum flame radius of 25% of the flame chamber radius R_0 [\[10,](#page-38-6) 33-[35\]](#page-41-6). This range is represented by filled circles in Figure [6.](#page-26-0) A direct comparison between experimental stretched flame speed and DNS data is performed and a very good agreement is then observed for all the equivalence ratios. For rich and stoichiometric conditions, the difference is marginal, especially for flame kernels free from ignition effects. For lean condition, the

difference is larger and on the order of 1 cm/s . Ignition of very lean mixtures requires high amount of energy to get spherical kernels which may affect the displacement speed $\widetilde{S_{d,b}}$ a little beyond the minimum flame radius of 1 cm. For flame radii larger than $2 \, cm$, the slope decreases progressively to become strongly negative. This confinement effect is visible both from the experiments and the simulations. This blind comparison confirms the capability of the 1D spherical DNS with GRI3.0 kinetic scheme to reproduce the dynamic of the flame front. Linear extrapolation (Eq. [19\)](#page-25-0) at zero stretch for lean and stoichiometric conditions, and a classical non-linear extrapolation (Eq. [20\)](#page-25-1) for rich conditions are used as recommended by [\[36\]](#page-41-7).

$$
\widetilde{S_{d,b}} = S_L^0 - \mathcal{L}_b K \tag{19}
$$

$$
\left(\frac{\widetilde{S_{d,b}}}{S_L^0}\right)^2 ln\left(\frac{\widetilde{S_{d,b}}}{S_L^0}\right)^2 = -2\frac{\mathcal{L}_b K}{S_L^0}
$$
\n(20)

It is worth noting that the Markstein Lengths \mathcal{L}_b in Eqs [19](#page-25-0) and [20](#page-25-1) are related to the density weighted displacement speed relative to burned gases, and differ from most of the data available in the literature by a factor equal to the density ratio, since $\widetilde{S_{d,b}}$ is considered instead of $S_{d,b} = dR/dt$.

⁵⁰⁰ A deviation of $S_L⁰$ from experiments with those from predicted by Cantera simulation is observed for all the cases and it is about 2-3 cm/s (Table [1\)](#page-26-1). This difference in S_L^0 between experiments (based on outwardly propagating spherical flame) and simulation (based on unstretched, adiabatic, freely-propagating planar flame) is commonly observed in the literature ([\[34\]](#page-41-8), Figure 3) and has been explained by many possible experimental biases: mixture preparation, ignition effect, radiation effect, extrapolation model, confinement effect. More surprisingly, S_L^0 values extrapolated from DNS data with the same range of flame stretch free from ignition and confinement effects are also lower than Cantera values, whereas the same kinetic scheme is used. Similar behaviors were observed previously for confined spherical expanding flames but never discussed. For instance, stoichiometric methane/air flames were simulated by [\[11\]](#page-39-0) with

Figure (6) Evolution of $\widetilde{S_{d,b}}$ with flame stretch at different equivalence ratios.

GRI3.0 mechanism with larger radius combustion chamber. $S_{d,b}^0$ was estimated at 268 cm/s , leading to $S_L^0 = 35.45$ cm/s , which is below the target given by 1D planar flame calculation. Similar observations can be found in [\[37\]](#page-42-0) and [\[39\]](#page-42-1) still with GRI3.0.

		S_L^0 [cm/s]	$\lceil \text{cm/s} \rceil$ σ_{S^0}	\mathcal{L}_b [mm]	$\sigma_{\mathcal{L}_b}$ [mm]	fit
$\phi = 0.7$	Cantera	18.49				
	Experiments DNS	16.82 17.28	0.036	0.030 0.085	0.0024	Linear Linear
$\phi = 1.0$	Cantera	36.30				
	Experiments	33.38	0.078	0.099	0.0022	Linear
	DNS	33.71		0.094		Linear
$\phi = 1.2$	Cantera	32.00				
	Experiments DNS	29.56 29.50	0.047	0.105 0.095	0.0011	Non-Linear Non-Linear

Table (1) Extrapolated flame speed from $S_{d,b}$ and corresponding Markstein length, \mathcal{L}_b , obtained from Eq. [19](#page-25-0) and [20](#page-25-1) by fitting $S_{d,b} = f(K)$ for tomographic radius between 0.8cm and 1.9cm.

5.2. Displacement speed relative to fresh gases, $\widetilde{S_{d,u}}$

Figure [7](#page-29-0) reports the evolution of experimental and numerical $\widetilde{S_{d,u}}$ over flame stretch rate at different equivalence ratios. As for $\widetilde{S_{d,b}}$, the flame speeds from the 10 measurements are averaged per class of stretch of $8s^{-1}$. The statistical approach used to report data allows a good and relevant comparison with the DNS. As mentioned previously, the routines developed by Varea et al. [\[14\]](#page-39-8) have been improved to reduce shot to shot variation and reliability of post processing. From Fig. [7,](#page-29-0) one can see an excellent agreement between both experimental and DNS data. Different observations can be done from the evolution of $S_{d,u}$ over stretch. First, the sensitivity to the ignition stage seems to be lower than for $\widetilde{S_{d,b}}$ since the flame speed spreads linearly towards smaller flame radii regardless the equivalence ratio. Second, a lower sensitivity to flame confinement effect is observed as the flame speed $\widetilde{S_{d,u}}$ behaves linearly for very large flame radii, excepted when the thermodynamic conditions P and T differ drastically from 530 the initial ones. Hence, considering the flame radius range $R_{min} - R_{max} =$ [0.8−2.4cm], extrapolations at zero stretch are more robust and less dependent of the flame radii range. Similar behaviors are observed also for the DNS. In order to be consistent to the extrapolation methodology used for $\widetilde{S_{d,b}}$, the following linear extrapolation (Eq. [21\)](#page-27-0) at zero stretch is used [\[2\]](#page-37-1),

$$
\widetilde{S_{d,u}} = S_L^0 - \mathcal{L}_u K \tag{21}
$$

 It is important to note that using traditional extrapolation formula for $\widetilde{S_{d,u}}$ (affected by thermal dilation) is not strictly correct, as pointed out by [\[38\]](#page-42-2). Consequently, such extrapolation performed (using a thermal dilatation affected value) may result in errors as pointed out by [\[28\]](#page-41-0). However, the zero stretch extrapolation of the experimental data converges with accuracy to the Cantera 1D values. The target values are reached for both DNS and experimental data for the three equivalence ratios. $\widetilde{S_{d,u}}$ measurement technique is shown to be not affected by the small size of the combustion chamber and therefore to confinement and ignition effects, allowing accurate measurements of

extrapolated values for low or intermediate chamber radii. Table [2](#page-28-0) summarizes the corresponding Markstein Lengths following Eq. [21](#page-27-0) from experimental and numerical data. One can see that both experimental and numerical values are in good agreement. Only few experimental data are available in the literature for comparison, but excellent agreement is found with previous works from the group, [\[14\]](#page-39-8), as well as more recent works from Bradley et al. [\[15\]](#page-39-3). From these \mathfrak{so} studies, \mathcal{L}_u for stoichiometric methane/air flame at ambient temperature and atmospheric pressure are very close to those obtained in this work, -0.12 mm and -0.11 mm, respectively. For their numerical work, Giannakopoulos et al. [\[2\]](#page-37-1) demonstrated that flame sensitivities to stretch were more dependent to the isotherm chosen when the fresh gas side was used compared to the burned gas side. In this study, we show that experimental measurements can report quantitative and accurate data on $\widetilde{S_{d,u}}$ and its associated extrapolated value when care is taken on the experimental protocol and post processing. Moreover, as mentioned by Jayachandran at al. [\[28,](#page-41-0) [30\]](#page-41-2) laminar burning velocities measured by $\widetilde{S_{d,u}}$ technique avoid any biases due to radiation, extrapolation procedure and density correction. Moreover, as long as inward flow exists due to confinement and/or sub or hyper adiabatic conditions [\[11\]](#page-39-0), $\widetilde{S_{d,u}}$ technique seems

to be a good candidate for accurate laminar burning velocities measurements. This is typically true when heavy/light fuels but also tailor made fuels are considered for which no kinetic schemes exist.

		S_L^0 [cm/s]	σ_{S^0} [cm/s]	\mathcal{L}_u [mm]	$\sigma_{\mathcal{L}_u}$ [mm]
$\phi = 0.7$	Cantera. Experiments DNS	18.49 18.36 19.13	0.19	-0.194 -0.135	0.014
$\phi = 1.0$	Cantera. Experiments DNS	36.30 35.72 36.71	0.48	-0.115 -0.084	0.015
$\phi = 1.2$	Cantera Experiments DNS	32.00 32.89 33.00	0.53	-0.069 -0.047	0.019

Table (2) Extrapolated flame speed from $\widetilde{S_{d,u}}$ and corresponding Markstein length, \mathcal{L}_u , obtained from Eq. [21](#page-27-0) by fitting $\widetilde{S_{d,u}} = f(K)$ for tomographic radius between 0.8 cm and .2 cm.

Figure (7) Direct comparison of density weighted displacement speed relative to fresh gases for experimental and DNS data.

$5.5.5.$ 5.3. Spatially averaged consumption speed, $\langle S_c \rangle$

The spatially averaged consumption speed of the deficient species is now reported from experimental measurements of flame radius R_T , obtained from tomographic recordings, and fresh gas density deduced from fresh gas velocity profile as presented above. This is reminded in Eq[.22.](#page-29-1)

$$
\langle S_c \rangle = \frac{dR_T}{dt} - \frac{(R_0^3 - R_T^3)}{3R_T^2} \frac{1}{\rho_u} \frac{d\rho_u}{dt}
$$
\n(22)

 We implicitly assume that the experimental flame radius R_T is equal to $R_{f,eq}$ in Eq. [7.](#page-7-2) This was already validated in [\[20\]](#page-40-0). Simultaneously, the spatially averaged consumption speed from the DNS can be exactly computed from the integral of the mass reaction rate of the deficient species, according to the developments in [\[19\]](#page-39-7) and [\[20\]](#page-40-0):

$$
\langle S_{c, DNS} \rangle = -\frac{1}{\rho_u Y_{k,u} R_{f,k}^2} \int_0^{R_0} \dot{\omega}_k r^2 dr \tag{23}
$$

 Equality between Eq. [22](#page-29-1) and Eq. [23](#page-30-0) was already numerically demonstrated in [\[20\]](#page-40-0). We present now the experimental measurements of $\langle S_c \rangle$ by Eq. [22](#page-29-1) and the comparison with the DNS data from Eq[.23.](#page-30-0) For the three different equivalence ratios, the spatially averaged consumption speeds are reported according to flame stretch (Figures [8,](#page-31-0) [9](#page-32-0) and [10\)](#page-33-0). At the same time, the first and the second term of the RHS of Eq[.22](#page-29-1) are also plotted both from the experiments and the DNS to validate the experimental determination of these two terms. $\langle S_c \rangle$ is calculated as the difference of two large numbers, and therefore its accuracy will depend directly on the accuracy of each contribution. For the first term, error bars are similar to those indicated for $\widetilde{S_{d,b}}$ which were mainly due to the shot-to-shot repeatability, multiplied by the density ratio. The second term has similar error bars. Both terms are well captured by the experiment, with stretched values that are very close to the DNS (slightly underestimated for $\phi = 1.0$ and 1.2, and quite clearly overestimated for $\phi = 0.7$). For high stretch values, this difference slightly increases, before diverging when the influence of ignition becomes predominant. The difference of these two contributions gives the spatially averaged consumption speed $\langle S_c \rangle$, which is in very good agreement with the consumption speed computed from the integral of the reaction rate. For stretched flames free from confinement and ignition effects, experiments and DNS values are superimposed. For $\phi = 0.7$, the agreement 595 is slightly worse, as already observed for $\widetilde{S_{d,b}}$. For this condition, ignition effect seems to persist beyond the usual minimum value of flame radius. The error bars on experimental $\langle S_c \rangle$ are slightly lower compared to those of the two contributions, which underlines the compensating effect when considering the shot to shot fluctuation. Stretched consumption speeds seem much less sensitive 600 to confinement effects than $\widetilde{S_{d,b}}$, with a globally linear behavior at large radii, observed both numerically and experimentally, with the range of flame radius

accessible through the chamber. The extrapolated values are similar to each other, slightly lower than the values given by the 1D calculation by Cantera. The slopes are also well captured by the experiments.

Figure (8) Direct comparison of spatially averaged consumption speed for experimental and DNS data, $\phi = 1.0$. DNS data are represented by continuous lines. Experimental data are reported in this figure with circle symbols. Red color is dR_T/dt , blue color is the density ratio term in Eq. [22](#page-29-1) and the spatially averaged consumption speed is represented in green by using Eq. [22](#page-29-1) for experiments and Eq. [23](#page-30-0) for the DNS. Linear extrapolations over the bold line and filled symbols are reported in dotted and dashed lines.

 Similarly to the density weighted displacement speeds, extrapolation at zero stretch of the spatially averaged consumption speed allows to introduce the Markstein length \mathcal{L}_c , according to the following linear equation,

$$
\langle S_c \rangle = S_L^0 - \mathcal{L}_c K \tag{24}
$$

Values of extrapolated flame speed and Markstein length are reported in

Figure (9) Direct comparison of spatially averaged consumption speed for experimental and DNS data, $\phi = 1.2$. DNS data are represented by continuous lines. Experimental data are reported in this figure with circle symbols. Red color is dR_T/dt , blue color is the density ratio term in Eq. [22](#page-29-1) and the spatially averaged consumption speed is represented in green by using Eq. [22](#page-29-1) for experiments and Eq. [23](#page-30-0) for the DNS. Linear extrapolations over the bold line and filled symbols are reported in dotted and dashed lines.

Table [3.](#page-32-1)

Table (3) Extrapolated flame speed from $\langle S_c \rangle$ and corresponding Markstein length, \mathcal{L}_c , obtained from Eq. [24](#page-31-1) by fitting $\langle S_c \rangle = f(K)$ on a specific tomographic radius range.

Figure (10) Direct comparison of spatially averaged consumption speed for experimental and DNS data, $\phi = 0.7$. DNS data are represented by continuous lines. Experimental data are reported in this figure with circle symbols. Red color is dR_T/dt , blue color is the density ratio term in Eq. [22](#page-29-1) and the spatially averaged consumption speed is represented in green by using Eq. [22](#page-29-1) for experiments and Eq. [23](#page-30-0) for the DNS. Linear extrapolations over the bold line and filled symbols are reported in dotted and dashed lines.

⁶¹⁰ The discussion about these results and the comparison with $\widetilde{S_{d,b}}$ requires some reminders about the definition of the spatially averaged consumption speed. As said previously, the spatially averaged flame speed is defined from the global consumption rate, obtained by integrating the fuel reaction rate throughout the whole flame volume, normalized by a reference surface ⁶¹⁵ $A = 4\pi R^2$. As the spherical flame has a finite flame thickness which changes during its propagation, the identification of this reference surface (*i.e.* the isotherm) is delicate and can strongly impact the dependence of this spatially

averaged consumption speed on flame stretch,

$$
\left\langle S_c \right\rangle_{R=R^*} = S_L^0 - \mathcal{L}_c^* K \tag{25}
$$

In this equation $\langle S_c \rangle_{R=R^*}$ is the spatially averaged consumption speed with a ⁶²⁰ reference surface equal to R^* and \mathcal{L}_c^* is the corresponding Markstein length. The influence of the isotherm on \mathcal{L}_c^* has been numerically shown by Giannakopoulos et al. [\[16\]](#page-39-4) for propane / air mixtures, and a similar behavior is now presented for methane/air flames (Figure [11\)](#page-34-0).

Figure (11) Effect of reference surface, expressed in flame radius and corresponding isotherm, on the Markstein lengths \mathcal{L}_c^* and \mathcal{L}_b . $\phi = 1$

In this work, it was decided to introduce a flame surface which does not suffer from any ambiguity and which is defined by an equivalent radius based on the total mass of fuel (if lean flame) or of oxidant (rich flame) [\[19,](#page-39-7) [20\]](#page-40-0), $R^* = R_{f,k}$. For this particular value of R^* , Eq. [25](#page-34-1) becomes equal to Eq. [24.](#page-31-1) We remind that this equivalent radius corresponds to an isotherm close to 600 K, and it is obtained experimentally from tomographic recordings. By considering Tables [1](#page-26-1) ϵ_{680} and [3,](#page-32-1) one can see the very small differences between the Markstein lengths \mathcal{L}_b and \mathcal{L}_c .

The evolution of numerical data of \mathcal{L}_c^* and \mathcal{L}_b according to the isotherm of the flame radius is plotted in Figure [11.](#page-34-0) $x = 0$ refers to the location of the maximum heat release, and $x = 0.55$ corresponds to the fresh gas side. The difference between these two Markstein lengths decreases when one approaches

towards the gases fresh, and cancels out when R^* is close to $R_{f,k}$. Thus, with this reference surface, the spatially averaged consumption speed is expected to be very similar to $\widetilde{S_{d,b}}$. Note that even if the lengths \mathcal{L}_b and \mathcal{L}_c are similar, the spatial averaged consumption speed is not sensitive to confinement effects, and 640 seems to exhibit a linear behavior at high equivalence ratio, unlike $S_{d,b}$. Note that this Markstein length \mathcal{L}_c is different from that introduced by asymptotic studies [\[16\]](#page-39-4), where the local consumption speed is considered (Eq. [1\)](#page-3-0). This Markstein length noted $\mathcal{L}_{c,Local}$ is systematically greater than the length \mathcal{L}_b and very weakly dependent on the fuel, according to the following relation [\[16\]](#page-39-4),

$$
\mathcal{L}_b - \mathcal{L}_{c,Local} = \left(\frac{1}{\sigma - 1} \int_1^{\sigma} \frac{\tilde{\lambda}(x)}{x} dx\right) \cdot l_f \tag{26}
$$

where σ is the thermal expansion ratio, $\tilde{\lambda}$ is the non-dimensional thermal conductivity and l_f is the flame reaction zone thickness estimated from the ratio of the thermal diffusivity of the fresh gases with the laminar flame speed.

6. Conclusion

This paper highlights the experimental tools which have been developed for measuring laminar flame speeds in the expanding flame velocity configuration (kinematic and kinetic velocities) whose definitions and expressions have been rigorously derived previously. These laminar flame speeds were measured for methane/air mixtures at different equivalence ratios and compared directly with DNS performed by A-SURF code simulating the exact geometry of the combustion chamber, in spherical 1D coordinates. This numerical approach allowed validation of all the post-processing steps, giving access to the local fresh gas velocity at the entrance of the flame front, as well as to the density of the fresh gases, and the values of the stretched laminar flame speeds. With this numerical database, the experimental measurements enable the following conclusions to be drawn about the relevance and the accuracy of the different flame speeds.

This work reports a new experimental approach to evaluate the spatially averaged consumption speed $\langle S_c \rangle$ for spherically expanding flames from tomographic flame radius and fresh gases density measurements, Eq. [\(22\)](#page-29-1). This methodology was derived recently from the global reaction rate normalized by a reference flame surface defined by an equivalent flame radius based on the total mass of fuel (if lean flame) or of oxidant (rich flame) [\[20\]](#page-40-0). The novelty of this work is associated to the experimental measurement of fresh gas density from the integration of the continuity equation through a material control volume. Considering the initial fresh gas density, the location of the boundary of the control volume and the fresh gas velocity, it is possible to report the temporal evolution of the fresh gas density with an excellent level of accuracy, as demonstrated by the direct comparison with the DNS. The spatially averaged consumption speed is very close to the flame speed $\widetilde{S_{d,b}}$ ⁶⁷⁵ with similar positive Markstein lengths. $\langle S_c \rangle$ is however less sensitive to flame confinement and behaves more linearly with flame stretch for rich conditions. Even interesting to report an experimental measurement of total fuel reaction rate, it seems therefore difficult to extend this technique to other fuel/air mixtures without any other preliminary validations, such as the equivalence ⁶⁸⁰ between tomographic flame radius and the equivalent flame radius, $R_{f,k}$. It is also important to note that this spatially averaged consumption speed differs from the local consumption speed introduced in asymptotic theories and used in 1D configurations, and must be considered as complementary.

The displacement speed $\widetilde{S_{d,u}}$ requires an accurate measurement of the maximum velocity of the fresh gases at the entrance to the flame front. In this paper, an important improvement of post-processing tools was carried out and validated by a direct comparison with DNS simulations. To our knowledge, this is the first time that the fresh gas velocity profiles across the flame front in spherical expanding flames have been compared directly with DNS. The experimental fresh gas velocity profiles overlap perfectly with the DNS, and the agreement with the stretched flame speed $\widetilde{S_{d,u}}$ is excellent. For the operating conditions (quasi equi-diffusive fuel/air mixtures), this flame speed

behaves linearly with stretch, and allows a direct estimation of the laminar burning velocity $S_L⁰$ by a linear extrapolation. This quantity is not influenced by confinement effects and does not underestimate the extrapolated flame speed S_{L}^{0} . Extension of this linear extrapolation to non equi-diffusive fuel/air mixtures requires additional tests and discussion. It is also worth noting that this method presents a quite important scatter in spite of the improvements made. It is then necessary to carry out a larger number of tests (here about ten) to converge.

⁷⁰⁰ The flame speed $\widetilde{S_{d,b}}$ is very easy to measure with the assumptions usually made (burnt gases at equilibrium and at rest), but remains very sensitive to the effects of flame confinement. In this geometry, extrapolation at zero stretch leads to a systematic underestimation of the laminar burning velocity $S⁰_L$ of the order of 1 to 3 cm/s , regardless of the equivalence ratio of the mixture. For small combustion chambers, this effect is noticeable even when respecting the classic radius range criteria for extrapolation. A careful look of the literature also shows that this phenomenon is observed even for larger combustion chambers. This quantity also requires an accurate knowledge of the fuel composition in order to determine the density of the burnt gases by a chemical equilibrium calculation. These remarks partly explain the disparities observed in the values reported in recent years.

Acknowledgements

Financial supports from the French National Research Agency, under the project 'RAFBIOALG (ANR-18-CE43-0009)' and National Natural Science Foundation of China (no. 51861135309) are gratefully acknowledged.

References

- [1] T. Poinsot, D. Veynante, Theoretical and Numerical Combustion, Third Edition (www.cerfacs.fr/elearning), 2011.
- [2] G. K. Giannakopoulos, A. Gatzoulis, C. E. Frouzakis, M. Matalon, A. G. Tomboulides, Consistent definitions of "flame displacement speed" and

"markstein length" for premixed flame propagation, Combust. Flame 162 (2015) 1249–1264.

- [3] F. N. Egolfopoulos, N. Hansen, Y. Ju, K. Kohse-Höinghaus, C. K. Law, F. Qi, Advances and challenges in laminar flame experiments and implications for combustion chemistry, Prog. Energy Combust. Sci. 43 (2014) 36–67.
	- [4] N. Hinton, R. Stone, Laminar burning velocity measurements of methane and carbon dioxide mixtures (biogas) over wide ranging temperatures and pressures, Fuel 116 (2014) 743–750.
- [5] C. Xiouris, T. Ye, J. Jayachandran, F. Egolfopoulos, Laminar flame speeds under engine-relevant conditions: Uncertainty quantification and minimization in spherically expanding flame experiments, Combust. Flame 163 (2016) 270 – 283.
- [6] F. Halter, Z. Chen, G. Dayma, C. Bariki, Y. Wang, P. Dagaut, C. Chauveau, Development of an optically accessible apparatus to characterize the evolution of spherically expanding flames under constant volume conditions, Combust. Flame 212 (2020) 165–176.
	- [7] A. P. Kelley, J. K. Bechtold, C. K. Law, Premixed flame propagation in a confining vessel with weak pressure rise, J. Fluid Mech. 691 (2012) 26–51.
- [8] W. Liang, F. Wu, C. K. Law, Extrapolation of laminar flame speeds from stretched flames: Role of finite flame thickness, Proc. Combust. Inst. 36 (2017) 1137–1143.
- [9] T. Shu, Y. Xue, W. Liang, Z. Ren, Extrapolations of laminar flame speeds from expanding spherical flames based on the finite-structure stretched flames, Combust. Flame 226 (2021) 445–454.
	- [10] M. P. Burke, Z. Chen, Y. Ju, F. L. Dryer, Effect of cylindrical confinement on the determination of laminar flame speeds using outwardly propagating flames, Combust. Flame 156 (2009) 771–779.

- [11] M. Faghih, Z. Chen, J. Huo, Z. Ren, C. K. Law, On the determination
- of laminar flame speed from low-pressure and super-adiabatic propagating spherical flames, Proc. Combust. Inst. 37 (2019) 1505–1512.
	- [12] Z. Chen, Effects of radiation and compression on propagating spherical flames of methane/air mixtures near the lean flammability limit, Combust. Flame 157 (2010) 2267–2276.
- [13] S. Balusamy, A. Cessou, B. Lecordier, Direct measurement of local instantaneous laminar burning velocity by a new piv algorithm, Exp. Fluids 50 (2011) 1109–1121.
- [14] E. Varea, V. Modica, A. Vandel, B. Renou, Measurement of laminar burning velocity and markstein length relative to fresh gases using a new postprocessing procedure: Application to laminar spherical flames for methane, ethanol and isooctane/air mixtures, Combust. Flame 159 (2012) 577–590.
- [15] D. Bradley, M. Lawes, M. E. Morsy, Flame speed and particle image velocimetry measurements of laminar burning velocities and markstein numbers of some hydrocarbons, Fuel 243 (2019) 423–432.
	- [16] G. K. Giannakopoulos, C. E. Frouzakis, S. Mohan, A. G. Tomboulides, M. Matalon, Consumption and displacement speeds of stretched premixed flames - theory and simulations, Combust. Flame 208 (2019) 164–181.
- [17] E. F. Fiock, C. F. Marvin, The measurements of flame speed, Chem. Rev. 21 (1937) 367–387.
	- [18] D. Bradley, A. Mitcheson, Mathematical solutions for explosions in spherical vessels, Combust. Flame 26 (1976) 201–217.
- [19] A. Bonhomme, L. Selle, T. Poinsot, Curvature and confinement effects for flame speed measurements in laminar spherical and cylindrical flames, Combust. Flame 160 (2013) 1208–1214.

- [20] A. Lefebvre, H. Larabi, V. Moureau, G. Lartigue, E. Varea, V. Modica, B. Renou, Formalism for spatially averaged consumption speed considering spherically expanding flame configuration, Combust. Flame 173 (2016) 235–244.
- [21] G. E. Andrews, D. Bradley, Determination of burning velocities: A critical review, Combust. Flame 18 (1972) 133–153.
	- [22] E. Varea, V. Modica, B. Renou, A. M. Boukhalfa, Pressure effects on laminar burning velocities and markstein lengths for isooctane–ethanol–air mixtures, Proc. Combust. Inst. 34 (2013) 735–744.
- [23] Z. Chen, M. P. Burke, Y. Ju, Effects of lewis number and ignition energy on the determination of laminar flame speed using propagating spherical flames, Proc. Combust. Inst. 32 (2009) 1253–1260.
- [24] G. Smith, D. Golden, M. Frenklach, N. Moriarty, B. Eiteneer, M. Goldenberg, C. Bowman, R. Hanson, S. Song, W. G. Jr., V. Lissianski, Z. Qin, Gri-mech homepage, http://www.me.berkeley.edu/gri mech/ (Gas
	- Research Institute). [25] Y. Wang, A. Movaghar, Z. Wang, Z. Liu, W. Sun, F. N. Egolfopoulos,
- Z. Chen, Laminar flame speeds of methane/air mixtures at engine conditions: Performance of different kinetic models and power-law correlations, Combustion and Flame 218 (2020) 101–108.
	- [26] H. Yu, W. Han, J. Santner, X. Gou, C. H. Sohn, Y. Ju, Z. Chen, Radiation-induced uncertainty in laminar flame speed measured from propagating spherical flames, Combustion and Flame 161 (2014) 2815–2824.
- [27] D. G. Goodwin, R. L. Speth, H. K. Moffat, B. W. Weber, Cantera: An object-oriented software toolkit for chemical kinetics, thermodynamics, and transport processes, <https://www.cantera.org>, 2021. doi:[10.5281/](http://dx.doi.org/10.5281/zenodo.4527812) [zenodo.4527812](http://dx.doi.org/10.5281/zenodo.4527812), version 2.5.1.

- [28] J. Jayachandran, R. Zhao, F. N. Egolfopoulos, Determination of laminar flame speeds using stagnation and spherically expanding flames: Molecular transport and radiation effects, Combust. Flame 161 (2014) 2305–2316.
	- [29] E. Varea, J. Beeckmann, H. Pitsch, Z. Chen, B. Renou, Determination of burning velocities from spherically expanding h2/air flames, Proc. Combust. Inst. 35 (2015) 711–719.
- [30] J. Jayachandran, A. Lefebvre, R. Zhao, F. Halter, E. Varea, B. Renou, F. N. Egolfopoulos, A study of propagation of spherically expanding and counterflow laminar flames using direct measurements and numerical simulations, Proc. Combust. Inst. 35 (2015) 695–702.
- [31] GUM: Guide to the expression of uncertainty in measurement, Joint 815 Committee for Guides in Metrology, 2008.
	- [32] I. Hughes, T. Hase, Measurements and their Uncertainties. A practical guide to modern error analysis, Oxford University Press, 2010.
- [33] D. Bradley, P. H. Gaskell, X. J. Gu, Burning velocities, markstein lengths, and flame quenching for spherical methane-air flames: A computational study, Combust. Flame 104 (1996) 176–198.
	- [34] Z. Chen, On the accuracy of laminar flame speeds measured from outwardly propagating spherical flames: Methane/air at normal temperature and pressure, Combust. Flame 162 (2015) 2442–2453.
- [35] T. Sikes, M. S. Mannan, E. L. Petersen, An experimental study: laminar flame speed sensitivity from spherical flames in stoichiometric ch4–air mixtures, Combust. Sci. Technol. 190 (2018) 1594–1613.
	- [36] A. P. Kelley, C. K. Law, Nonlinear effects in the extraction of laminar flame speeds from expanding spherical flames, Combust. Flame 156 (2009) 1844–1851.
- 830 [37] Z. Chen, On the extraction of laminar flame speed and markstein length from outwardly propagating spherical flames, Combust. Flame 158 (2011) 291–300.
	- [38] J. H. Tien, M. Matalon, On the burning velocity of stretched flames, Combust. Flame 84 (1991) 238–248.
- [39] J. Beeckmann, R. Hesse, J. Schaback, H. Pitsch, E. Varea, N. Chaumeix, Flame propagation speed and markstein length of spherically expanding flames: Assessment of extrapolation and measurement techniques, Proc. Combust. Inst. 37 (2019) 1521–1528.

Declaration of interests

 \boxtimes The authors declare that they have no known competing financial interests or personal relationships that could have appeared to influence the work reported in this paper.

☐The authors declare the following financial interests/personal relationships which may be considered as potential competing interests: